An overview of the machines

	HV	ECO-Maxi
Areas of application	Surgical implants: large dimensions Stents	Rapid Shell Modelling: Small batches / laboratories
Special features	Very gentle processing	Cost-efficient versatile tool for small series with very short processing times, simple operation

Vibrator HV 20

- ► Process containers with PU lining
- ► Speed control via frequency inverter
- ► Container volume 23 litres
- Digital display of speed and process duration
- ► Automatic reversal of the direction of rotation

- Dosing pump
- Seperation sheets with transform teh main process chambers into smaller chambers for single processing

- ► LCD display of speed and process duration
- ► Speed control via frequency inverter
- ► Bayonet fitting for container attachment
- ► Automatic container detection and thereby speed range adaptation
- ► Automatic change of the direction of rotation in the magnetic mode



Founded in 1996, OTEC has quickly established itself in the market with new machine concepts, innovations and advancements. Around 20 % of the OTEC workers are employed in the R&D sector. For each market sector served, OTEC offers precisely matched and customized machine designs which are both efficient and precise in their handling and processing, far exceeding traditional methods of finishing. With its global network of highly trained representatives and certification to DIN 9001, OTEC guarantees the highest level of communication and process quality at all times.

THE COMPANY

Visibly better!

Form your own impression of the performance capability of our different machine series. Simply send us a sample part that we can process in our laboratory. We will send you a comprehensive report, customized to your applicaton, complete with details on the grinding and polishing media used and process paramter settings, available in 12 different languages.

Naturally at no cost or obligation and absolutely confidential. Request proof of the better technology.



		Bearbe	itungspro	otokoll	OTEC
Hander: Kurde Angenisfanter Rutestangen Perstantangen Perstanten Testante	Popegal La Mi Vilalo 64.02.2607 20.02.2607 5039 5059	National Index Index Tradigite Workshown Norge Nation	a Palanan Nacion C	Mushingsorishen ing santiga Mi Bigaya pulater colorian/of Saltysten Wasarka/Salt Corport dasser Ancertalist Henal	
_	-	Proc	ess-Rep	ort	Ότες
Cathener Warager Data monical Processed on: Report worker: Test-no:	NR: VNety 04.62.3007 32.63.3007 8229 2730	Regatement Workproce name: Guantity: Material	antariag per constant den	Offens Treasol aith Magnet Pulaher: Gap Soulen Statu-Nac Conjeantel Mater Concertration Internal	
	Пр	отокол пр	оцесса	обработки	OTEC
Парадина «Градая Паралия» Окантиваний рай Обранциотрин (д Обранциотрин (д Протиски намер «Пр Тактичнир «Такт Ки	ne: Penteh (JA Nami Wi VBAy na) 0422327 ane: 81829 name: 81829 t 3180	Ofgaste, nov Jähn stjoch Hotapen Ho Rahvertet Henopert	ng - Ofgenosy Ann 2 Luc polytrog mana B crame	Процесси изволяемости. Прогожа Прегода Прегода Самара Самара возна (облас) Концентрация околорицая Интернал	

OTEC Präzisionsfinish GmbH | Dieselstraße 8-12 | 75334 Straubenhardt-Feldrennach | Germany Telephone +49 7082 4911-20 | Fax +49 7082 4911-29 | E-mail: info@otec.de | www.otec-online.com

The fine surfaces

Perfect surfaces. Worldwide.







An overview of the machines

Surface finishing from the market leader

In medical and dental technology

THE PROCESS

Whether centrifugal disc finishing process (CF) or drag finishing process (DF): OTEC has developed high-quality machines for both mass finishing which ensure perfect work piece surfaces in medicine and dentistry. And up to 10-times more effective than conventional processes.

OTEC offers its machines in various sizes, from table-top units for efficient small series production to industrial large series - as required. Thus OTEC machines are ideal for numerous areas of application of medicine and dental technology such as surgical implants (bone plates, bone screws and joint implants), dental implant, teeth, dental tools and orthodontic products but also for ear shells and stents in vascular surgery. In addition to the machines, OTEC supplies the appropriate polishing and grinding media for optimal results.

Advantages at a glance

- ► Efficient for small and large series processing
- ► Process security
- ► Homogenous surface processing "better than hand polishing"
- ► Up to 10 times more effective
- ► Specially customized machine equipment for medical technology



- 1				
		CF	CF-T	CF-SP
	Areas of application	Surgical implants: for industrial batch production	Surgical implants: large dimensions, small batches	Surgical implants: smaller dimensions/geometry
		Orthodontic and dental tools in small to medium dimensions	Dental implants, smaller quantities Medical technology in general	Dental implants
	Special features	Patented gap system, absolute process security, high efficiency batch processing, simple operation	Compact and small, processing and machine quality of the "large ones" in table-top format, simple operation	Advancement of CF technology, grinding and polishing without changing the container or media, simple operation Water and compound input adjustable using the touch panel -> high process relaiability

- Process containers with hot molded PU lining
- High-quality gap system with ceramic rings for using extra-fine polishing granulate
- ► Aluminium profile chassis easy to add on optional equipment
- ► Speed control via frequency inverter
- Digital readout of preset time, elapsed time, speed and faults (CF-T only) ▶ PLC touch screen control unit with digital display of processing time, speed, rinse cycle, dosing, and other important process parameters and storage for up to 75 different processing programs. (not for CF-T)
- ► Automatic completion of grinding and polishing process thanks to flexible programming of the water flow and the compound concentration during the process (only for CF-SP).

- Dosing unit for the automatic preparation of the water/compound mixture or dosing pump with suction nozzle and automatic cut-out when empty (CF-T)
- Display of water flow on the control system. (CF, CF-SP)
- Drawer system for the storage of additional media containers (CF, CF-SP)
- ► Manual separator unit using a manual screen (CF, CF-SP) ► Spray system prevents the workpieces from coming to rest on the rim of the container and
- not being processed. (CF, CF-SP)
- ► Automatic separator unit using screening machine with vibration motor

Extensive machine and accessory information under www.otec-online.com or further options on request.

▶ Automatic rinsing unit. Pre-selection of the compound concentration using the control system.

An overview of the machines

	DF SERIES "dry/wet"
Areas of application	Endoscopy
	Femurs
	Orthodontic and dental tools
	Surgical implants such as tibias, hip joint, heart valves, etc.
Special features	The angled holders produce optimal surfaces even for complex geometries

Drag-finishing machines DF wet/dry

- ▶ Process container DF 3/4 150 litres fill volume, DF 5/6 220 litres, DF 8/10 300 litres
- ► Inside of process container PU-coated for minimal wear (only DF wet)
- ► Stable main frame of aluminum profile
- ▶ High-value and airtight steel cladding, painted on the outer walls and floor
- ► Quick change of the process container
- ► Vertical spindle with ball screw drive for 100 % duty cycle
- ► Display and pre-selection of the vertical work piece position
- ► Storage of 200 programs
- Greater clearance between the top edge of the container and the holder, for easier loading of holder
- ▶ 3, 4, 5, 6, 8 or 10 clamping devices for holding work piece holders
- ► Reinforced bearing for holder weights up to 15 kg
- ▶ Backup of the programs on external MMC card

Immersion depth control

• For the control of the immersion depth of the work pieces in the grinding/polishing media

Dosing unit (only DF wet)

▶ For the automatic preparation of the water/compound mixture with automatic rinsing unit. Pre-selection of the compound concentration using the control system. Display of water flow on the control system.

Holder with independent rotation

With these holders which were especially developed for tool processing, every work piece rotates independently during processing. This achieves an even processing quality in a significantly shorter process time.

Angled holders

Especially suited for the processing of face surfaces (e.g. for tibias).

Additional drive

Thereby work piece and rotor speed can be adjusted independently of each other and achieve optimal grinding and polishing results.

Water cooling

- ► For the reduction of granulate temperature
- ► Especially suited during the usage of polishing granulates

Areas of application

Surgical Implants

For high-strength implant materials such as CoCr, various stainless steel alloys, as well as ceramics and plastics. Our machines create perfect surfaces with the smallest surface roughness in a system-secure and efficient manner according to the demands of modern surgery.

The machines

Joint implants, tibias, femurs: DF dry, DF wet	Page
Bone plates: HV 20 (up to 500 mm long), CF, CF-T (80 - 120 mm)	Page
Bone screws, small bone plates: CF-SP, CF-T	Page

Dentaistry

For the various dentistry materials as well as very small work pieces from soft to hard. OTEC machines are perfectly suited to the demands of dentistry:

- Dental implants
- ► Teeth
- Dental tools
- Orthodontics products

Machine and processing information Implants, teeth: CF-SP, CF-T Dental tools, orthodontic products: CF

Page 10 Page 12

4 6 8

Ear Shells

For the contour-precise grinding of extremely rough surfaces as well as for the creation of very fine plastic surfaces.

Special processes and machines: CF, ECO-Maxi

Page 14

Page 14

Stents

For the soft and gentle burring of parts of light compositions, also in the poorly accessible inner side. Without crushing and pulling, without jamming.

Special processes and machines: HV 20

Machine overview.

Areas of application and equipment features

from page 15









Surgical implants: Joint implants, tibias, femurs ...

Perfect high shiny polished surfaces, not the smallest scratch and surface roughness of 0.01 µm with absolute process security, also for highly complex open form surfaces. That distinguishes the drag-finishing machine DF from OTEC. Depending on grinding and/or polishing granulate, maximum surface shine can be achieved with the most diverse materials. OTEC is currently the only manufacturer in a position to achieve perfect surfaces also for ceramic implants.

Ra: 1,23 μm Rz: 7,9 μm	million and many when any and the many	man hundred when my
Oberfläche na	ch OTEC-DF-Bearbeitung	Enlarged 125 times







Absolutely free of scratches. A high-gloss polished knee joint with Ra values up to 0.01 μm

THE MACHINES

DF wet / DF dry

Wet and dry processes for even abrasion or for absolute high gloss polishing. Due to the fast motion, high surface pressures are created between the workpiece and the processing medium. This creates very smooth surfaces which result in the high gloss finish of hand polishing in a very short time and with the highest degree of process stability. Depending on the material to be processed, any combination of wet and dry processes can be used. Available in a wide range dimensions and sizes - matched to the respective work piece to be processed.

Special features

For the multi-stage DF machines the change from wet to dry processing occurs automatically without interrupting the finishing process. The total process is accelerated.

Angled and driven holders guarantee an all around processing into the smallest corners such as for tibias. Thus perfectly smooth surfaces are also achieved in work piece under cuts.

Advantages

- ► Surfaces under 0.02 µm in extremely short processing time
- ► Highly cost-effective
- ► Automatic change from wet and dry processing
- ► Very compact design with high output
- Process-reliable
- ► Simple operation
- ► Surfaces free of defects

For further information and basic equipment, see page 16.



Current manufacturing process



DF processing

The DF simplifies complicated process steps. Particularly for open spaces, this procedure achieves better and more reliable and consistent results. In the end, the resultant finish exceeds the smoothness that an be achieved using hand polishing, without scratches or orange peel. The process is extremely efficient, while also producing better results.



Surgical implants: Bone plates, precision in the surface

OD

Ideal for smooth, generously rounded and homogeneous surfaces of bone plates which often require a particularly large edge rounding. OTEC has the perfect solution for both small and large bone implants. The high-performance vibrator HV 20 from OTEC (for larger work pieces) and the CF machines (for smaller work pieces up to 100 mm). For the grinding of punching and chipping traces in very short processing time. The result: High-quality, precise bone plate surfaces in every size.

 $\triangleright 6$



For large bone plates: the HV 20 (up to 500 mm long) With the principle of a vibrator, the high-performance vibrator HV 20 creates perfect surfaces due to a homogeneous abrasion and is up to 65 % faster than comparable machines. Adjusted to work piece and media, it operates with exactly defined oscillations which produce a vibratory grinding effect due to relative motion of abrasives and work piece. Depending on machine geometry, bone plates up to 500 mm in length can be processed.

Advantages:

- ► Especially for large bone plates up to 500 mm in length
- ▶ Up to 65 % faster than comparable machines on the market

For small bone plates: the CF, or the CF-T (from 0 - 80 mm)

High-performance centrifugal disc finishing machines, the CF-T in compact table-top design. The unique, patented gap system between the disc and the process container enables the gap to be set with an accuracy of 0.05 mm when using the CF machine for dry processing. This means that very thin work pieces can be processed and that the very best results can be achieved by using extremely fine abrasive media. And all that for a very attractive price-performance ratio. A recent enhancement to the CF-T is the CF-SP for surgical implants which is described in the following sections p. 9

Advantages:

- ▶ Especially for smaller bone plates (up to 80 mm in size) and small quantities
- ► Compact table-top design
- ▶ Patented gap system for the usage of very fine polishing media

For further information and basic equipment, see page 15 and 17.

▶ OTEC-SERIES: HV







▶ Multiple work steps in one: from burring to wet polishing with a high-gloss surface of Ra: < 0,04 um

Surgical implants:

Bone plates and bone screws

The CF series machines are particularly suited for the treatment of implants made from stainless steel or titanium alloys as well as plastics and ceramics. Work pieces can be reliably deburred without appreciably rounding the corners in the process, which is very important for bone screws. OTEC has developed a special process in order to achieve a smoothing of the surfaces with subsequent polishing in the µm range, which can all be done in one process. Ra values of 0.02 µm are possible here. The CF series is also suited for the complete rounding of bone plates.









Dentistry:

Implants, teeth

Deburring without appreciable edge rounding

Deburring and creation of smooth surfaces are essential in dentistry. Therefore the CF-SP and CF-T are the ideal devices when implant surfaces and teeth made from stainless steel and titanium alloys as well as ceramic must be smoothed and polished - perfectly completed to the μ m range. The process developed by OTEC allows for Ra values of 0.03 μ m - and all that in one single work step.



The new CF-SP

With this centrifugal disc finishing machine, wet grinding and polishing can occur in succession without changing the container or media, completely without conversion or changing of the media. This offers time savings and makes perfect sense with a high degree of process reliability and repeatability. Deburring, grinding, and high-gloss polishing of the work piece: all in one single step.

Advantages:

- Wet grinding and polishing in one step without container or media change and filtering.
- Previously unachieved high efficiency
- Designed for industrial large batchs
- Process-reliable

The CF-T

Very compact table-top machine for the cost-effective finishing of perfect surfaces particularly for smaller series and single processing in research and development. The patented gap system between the circular disc and the process container makes the CF-T particularly suited for small and flat workpieces. Any lodging and damaging of these work pieces during the finishing process is eliminated completely.

Advantages:

- Very compact table-top design
- \blacktriangleright Ideal for smaller batches and single piece processing in research and development
- ► Patented gap system which protects against lodging
- Process-reliable
- ► Simple to handle and operate

For further information and basic equipment, see page 15.







processed

unprocessed



Implant screws, perfectly deburred, ground and polished to a high gloss - processed in one single work step with the OTEC machine CF-SP - and the sharp edges remain.



Fine and soft ceramic or plastic surfaces such as tooth implants in small and large series. It is particularly important here that deburring, smoothing, and polishing occur without appreciable edge rounding.

Dentistry: Orthodontic and dental tools

Your perfect route to the perfect tool

The appropriate process for every tool: Whether sharp-edged or edge-rounded, pointed or dull -CF series OTEC machines produce perfect surfaces for every application area. Using appropriately selected grinding and polishing media, the CF series machines produce high gloss finishes normally achieved only through hand polishing, all in a very short time on both large and small work pieces.





Brackets -Durable and ready-to-use thanks to perfect polishing.

Wires Inner wires with efficiently treated surfaces without deformation or damage occurring.

Orthodontic Tools Perfect surfaces for perfect instruments.



processed unprocessed



CF-series

Ideal for sharp-edged orthodontic and dental tools with highly polished, finished surface without appreciable edge rounding. CF machines take care of deburring, grinding and polishing of even the smallest work pieces in one step. Using suitable polishing granulate in an open top container in the smooth grinding process, the tools move in a toroidal motion which creates a gentle movement through the media while the parts are ground and polished. This produces the high gloss without the products losing their sharp edges.

Advantages:

- Previously unachieved high efficiency
- ► Several work steps without changing the container or media.
- ► Designed for industrial large batches
- ► Guaranteed process reliability

For further information and basic equipment, see page 15.

► Wet grinding and polishing in one step without changing the equipment.



Ear shells (Rapid Shell Modelling) for hearing aids

Surfaces for custom-fit perfection

THE MACHINES

Surfaces of ear shells are initially too rough to guarantee proper fit and comfort in the human ear. OTEC machines grind and polish the plastic surfaces both gently and with guaranteed process reliability in the shortest time. This replaces the time-consuming and difficult manual grinding process.

For industrial processing: the CF

- A patented gap system enables the usage of very fine polishing media
- 75 individual processing programs can be stored
- Serial efficient processing

For laboratories and small patches: the ECO-Maxi

- Cost-efficient versatile tool for small batches
- Wet, dry and magnet polishing
- ► Short processing times
- Small foot print



Stents

The delicate surface finishing

The HV 20

The light construction of these work pieces sets stringent requirements for the processing. Thus stents may not be deformed during processing. The poorly accessible inner surfaces must also be deburred. HV 20 takes care of this. The high-power vibrator guarantees a homogeneous abrasion and processing of the stents which is both suitable and gentle.

Advantages:

- Suitable for industrial processing of small and large parts
- Very gentle processing
- Process-reliable
- Absolutely high-quality surfaces
- Good inner processing

